

# Update on IEEE 802.3BA 40 and 100GE

Henk Steenman

[Henk.Steenman@ams-ix.net](mailto:Henk.Steenman@ams-ix.net)



# IEEE-SA Standards board operations manual Jan 2005


At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position, explanation, or interpretation of the IEEE



# Milestone: IEEE 802.3ba

## Draft version 1.0

- ▶ Long document (292 pages)
- ▶ Does capture all the objectives
- ▶ Technical specifications could and will be modified and or clarified as implementations take off.
- ▶ Lot of editorial work still necessary
- ▶ Draft 2.0 will be technically complete and go up for WG ballot
  - ▶ *Scheduled for march 2009*
- ▶ When schedule will hold, the standard for both 40 and 100GE will be delivered June 2010




# ***Reach objectives and physical layer specifications***


	<b>40GE</b>	<b>100GE</b>	<b>Solution</b>
1m Backplane	40GBase-KR4	*	4 X 10 Gbit/s (reuse 10GBase-KR)
10m Copper	40GBase-CR4	100GBase-CR10	n X 10 Gbit/s (reuse 10GBase-KR)
100m OM3 MMF	40GBase-SR4	100GBase-SR10	n x 10 Gbit/s
10km SMF	40GBase-LR4	100GBase-LR4	4 x 10 Gbit/s 4 x 25 Gbit/s
40km SMF	*	100GBase-ER4	4 x 25 Gbit/s

# Optical Transport Network

- ▶ One of the objectives is to provide “appropriate support for OTN”
  - ▶ *40GE: define transparent mapping of 40GE into existing ODU3*
    - ▶ Transcoding to be specified by ITU-T SG15
    - ▶ Coordination between ITU-T and IEEE on control block types
  - ▶ *100GE: ITU to define a new ODU4 tier*



# 40GE, 100GE architecture



AN = AUTO-NEGOTIATION

CGMII = 100 Gb/s MEDIA INDEPENDENT INTERFACE

FEC = FORWARD ERROR CORRECTION

LLC = LOGICAL LINK CONTROL

MAC = MEDIA ACCESS CONTROL

MDI = MEDIUM DEPENDENT INTERFACE

PCS = PHYSICAL CODING SUBLAYER

PHY = PHYSICAL LAYER DEVICE

PMA = PHYSICAL MEDIUM ATTACHMENT

PMD = PHYSICAL MEDIUM DEPENDENT

XLGMII = 40 Gb/s MEDIA INDEPENDENT INTERFACE

NOTE1—CONDITIONAL BASED ON PHY TYPE

- Consistent with existing Ethernet architecture
- Same frame format
- Changes are below the MAC
- New interface definitions



# 40GBase-CR4, 100GBase-CR10


- ▶ Reusing the 10GBase-KR architecture (802.3ap)
  - ▶ *40GBase-CR4: 4 x 10Gbit/s*
  - ▶ *100GBase-CR10: 10 x 10Gbit/s*
- ▶ Cable parameters based on 10GBase-CX4
- ▶ Autonegotiation
- ▶ Connector
  - ▶ *4 x MDI : QSFP*
  - ▶ *10 x MDI: SFF-8092*



# 40GBase-SR4 and 100GBase-SR10


## 100m OM3 MMF

- ▶ 40GBase-SR4
  - ▶ *4 parallel lanes for both Tx and Rx of over 4+4 parallel fibers*
  - ▶ *Connector is high density small form factor*
- ▶ 100GBase-SR10
  - ▶ *10 parallel lanes for both Tx and Rx of over 10+10 parallel fibers*
  - ▶ *Connector is high density small form factor*
- ▶ There seems to be a lot of interest in going beyond 100m
  - ▶ *Ongoing debate on how far the adopted proposal can actually go?*  
*for example over OM4 MMF*






# 40GBase-LR4



- ▶ CWDM baseline grid
- ▶ ITU G694.2
- ▶ 1270, 1290, 1310, 1330nm

# 100GBase-LR4




► LAN WDM baseline grid

► *ITU G694.1*

► 1295, 1300, 1305, 1310

# 100GBase-ER4




► LAN WDM baseline grid


► *ITU G694.1*

► 1295, 1300, 1305, 1310

# Where is the standard process now?



# IEEE802.3ba Task Force timeline



# Next meetings

- ▶ November 2008 meeting
  - ▶ November 9 - 14 Dallas, TX
  - ▶ Draft 1.0 comment resolution, working towards Draft 2.0
- ▶ Januari 2009 meeting
  - ▶ Januari 12 - 16 New Orleans
- ▶ March 2009 plenary
  - ▶ March 8 - 13 Vancouver
- ▶ More information on:
  - ▶ <http://grouper.ieee.org/groups/802/3/ba>





# Questions?

